

K795T



15" Freestanding Information Kiosk



- Powered by Flytech Rugged Metal Panel PC
- Quick-Service by Swapping All-in-One Panel PC
- Industrial Powder Coating
- Stylish Slim and Small Footprint Design
- The Most Cost Effective Kiosk Model
- Fanless Design for Noise Free Environment



Features



Swappable Panel PC for Easy On-site Service



SECC black or Stainless steel Panel PC meets NEMA 4 / IP65 Water & Dust proof at front display



Rear Access Door With Locks and Keys for quick maintenance



Rich I/O ports provide excellent peripheral connectivity

K795T



Specification

Model Name	K795T
Mainboard	B68
CPU Support	Intel® Atom™ N270 Processor 1.6GHz L2 512K FSB 533MHz
Chipset	Intel® 945GSE Express + ICH 7M
System Memory	2 x DDR2 DIMM up to 2GB FSB 533MHz
Graphic Memory	Intel® GMA 950 share system memory up to 224MB
LCD / Touch Panel	
LCD Size	15" TFT LCD
Brightness	250 nits (350 nits optional)
Maximal Resolution	1024x768
Touch Screen Type	Resistive / SAW / IR / Temper glass
Storage	
HDD	2.5" Slim HDD bay
Flash Memory	Optional Compact Flash memory (without HDD)
Expansion	
Mini-PCI	1
External I/O Ports	
USB 2.0	4
Serial / COM	4 x RJ-45 (COM3 & COM4 pin 1/9 with 5V or 12V powered by Jumper)
Parallel	1
LAN (10 / 100Mbps)	1
Cash Drawer	1 (12V or 24 V)
DC Jack	1
Audio Jack	1 x Line-out, 1 x MIC-in
PS/2	1
Internal Interface	
USB 2.0	2
Power	
Power Adapter	DC 19V, 90W
Environment	
EMC & Safety	FCC, Class A, CE, LVD
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	5% ~ 95% RH non condensing
Storage Humidity	5% ~ 95% RH non condensing
Dust & Water Proof	NEMA 4 / IP65 in front bezel
Dimension (W x D x H mm / inch)	400 x 460 x 1353 mm / 15.7" x 18.1" x 53.3"
Weight (kg / lbs)	38 kgs / 83.8 lbs
Mounting	100mm x 100mm Standard VESA mounting holes
OS Support	Windows XP, WEPOS, XP Embedded, XP Professional for Embedded, WIN 2000 Professional Embedded, Embedded Linux

Product specifications subject to change without prior notice.

©2011 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.

FLYTECH

FLYTECH Technology Co., Ltd.
No.168, Sing-ai Rd.,
Neihu District, Taipei City 114,
Taiwan
Tel: 886-2-8791-4988
Fax: 886-2-8791-4966
E-mail: sales@flytech.com.tw
www.flytech.com

U.S.A. - California
47825 Warm Springs Boulevard, Fremont, CA 94539, USA Tel: 1-510-257-5180 Fax: 1-510-257-5181 E-mail: sales@flytech.com
China - Shanghai
3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China
Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 http://www.flytech.com.cn E-mail: sales@flytech.com.cn
China - Hong Kong
Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd., Kowloon Bay, Kowloon, Hong Kong
Tel: 852-3525-5800 Fax: 852-2751-7447 http://www.flytech.com.hk E-mail: sales@flytech.com.hk

1104 - K795a